

Primary lithium batteries

Li-SOCl₂ range



Li-SOCl₂ cells

Production site	Size	Open circuit voltage	Nominal voltage	Nominal capacity (drain) (2.0 V cut-off)	Maximum recommended continuous current	Operating temperature range	Outside diameter max.	Height max.	Typical weight	UL recognition	Transport status
-----------------	------	----------------------	-----------------	--	--	-----------------------------	-----------------------	-------------	----------------	----------------	------------------

Small LS cells

LS 14250	UK-F-PRC	½ AA	3.67 V	3.6 V	1.2 Ah (1 mA)	35 mA	-60/+ 85°C*	14.55 mm	25.15 mm	8.9 g	yes	Non-restricted
LS 14250W	F-PRC	½ AA	3.67 V	3.6 V	1.2 Ah (1 mA)	20 mA	-60/+ 95°C*	14.55 mm	25.15 mm	8.9 g	yes	Non-restricted
LS 14500	UK-F-PRC	AA	3.67 V	3.6 V	2.6 Ah (2 mA)	50 mA	-60/+ 85°C*	14.55 mm	50.30 mm	16.7 g	yes	Non-restricted
LS 14500Ex	UK-PRC	AA	3.67 V	3.6 V	2.6 Ah (2 mA)	50 mA	-60/+ 85°C*	14.55 mm	50.30 mm	16.7 g	yes	Non-restricted
LS 14500W	F-PRC	AA	3.67 V	3.6 V	2.6 Ah (1 mA)	30 mA	-60/+ 95°C*	14.55 mm	50.30 mm	16.7 g	yes	Non-restricted
LS 17330	UK	¾ A	3.67 V	3.6 V	2.1 Ah (3 mA)	25 mA	-60/+ 85°C*	16.50 mm	33.40 mm	14.4 g	yes	Non-restricted
LS 17500	F	A	3.67 V	3.6 V	3.6 Ah (3 mA)	100 mA	-60/+ 85°C*	17.13 mm	50.90 mm	21.9 g	yes	Non-restricted

*Cells leakproof up to +120°C

Large LS cells

LS 26500	F	C	3.67 V	3.6 V	7.7 Ah (4 mA)	150 mA	-60/+ 85°C*	26.00 mm	49.1 to 50.4 mm***	48 g	yes	Class 9
LS 33600**	F	D	3.67 V	3.6 V	17.0 Ah (5 mA)	250 mA	-60/+ 85°C*	33.40 mm	60.2 to 61.6 mm***	90 g	yes	Class 9

*Cells leakproof up to +120°C

**Low Magnetic cell versions available

***Depending on cell finish

LSH spiral cells

LSH 14	F	C	3.67 V	3.6 V	5.8 Ah (15 mA)	1.3 A	-60/+ 85°C*	26.00 mm	50.40 mm	51 g	yes	Class 9
LSH 14 "light"	F	C	3.67 V	3.6 V	3.6 Ah (15 mA)	1.3 A	-60/+ 85°C	26.00 mm	50.40 mm	51 g	—	Non-restricted
LSH 20**	F	D	3.67 V	3.6 V	13.0 Ah (15 mA)	1.8 A	-60/+ 85°C*	33.40 mm	61.60 mm	100 g	yes	Class 9
LSH 20-150	F	D	3.67 V	3.6 V	14.0 Ah (300 mA)***	300 mA	-40/+ 150°C	32.05 mm	61.70 mm	104.5 g	—	Class 9
LSH DD-150	F	DD	3.67 V	3.6 V	28.0 Ah (600 mA)***	600 mA	-40/+ 150°C	33.0 mm	125.5 mm	215 g	—	Class 9

*Cells leakproof up to +120°C

**LSH 20 HTS cell version available

***Nominal capacity at +150°C

All LSH cells are fitted with individual 5 Amp fuse protection

Primary cells and batteries are not rechargeable.

Their internal impedance may rise versus time, especially in case of exposure at elevated temperature.



saft

Li-SOCl₂ Military battery packs

	Cell type construction*	Open circuit voltage	Nominal voltage	Voltage cut-off	Rated capacity	Maximum dimensions	Typical weight	Safety features	NATO Stock Number (NSN)	Typical applications
PS 40 A	4s1p LSH 14	14.7 V	14.0 V	10.0 V	4.6 Ah	108 x 65 x 49 mm	285 g	PTC 1.1 A**	6135-14-420-1760	Radiocommunication (TRPP 11/13)
PS 42 A	2s1p LSH 20	7.3 V	7.0 V	5.0 V	9.0 Ah	69.9 x 67.2 x 34 mm	230 g	PTC 3.5 A**	6135-14-434-0766	Radiocommunication (TRPP 39)
PS 48 B	5s2p LSH 20	18.3 V	17.5 V	12.6 V	18.0 Ah	212.4 x 72.7 x 68.5 mm	1150 g	PTC 1.85 A**	6135-14-451-7198	Radiocommunication (TRC 350)
PS 52 A	2s1p LSH 20	7.3 V	7.2 V	5.0 V	12.5 Ah	77.5 x 63.5 x 34.6 mm	225 g	PTC 2.0 A**	6135-14-459-9265	Radiocommunication (Portable PR4G)
PS 53 B	6s1p LSH 20	22.0 V	21.0 V	15.0 V	12.5 Ah	210.5 x 68.5 x 37.5 mm	720 g	PTC 2.5 A**	6135-14-459-9266	Radiocommunication (Portable PR4G)

* Xs Yp = Y parallel branches of X cells in series per branch

** Maximum hold current

Li-SOCl₂ Civil battery packs

	Cell type construction*	Open circuit voltage	Nominal voltage	Rated capacity	Maximum dimensions	Typical weight	Typical applications
LS 14250 MLB	1s1p LS 14250	3.67 V	3.6 V	1.2 Ah	16.8 x 28.6 mm	15 g	Metering, professional electronics
LS 9V	3s1p LS 14250	11.0 V	10.8 V	1.2 Ah	49.1 x 46.8 x 26.8 mm	29 g	Memory back-up, metering, smoke detectors, professional electronics
Lithopack	2s1p LS 14500	7.3 V	7.2 V	2.6 Ah	56.6 x 31.6 x 17.3 mm	34 g	Memory back-up, metering, professional electronics

Primary cells and batteries are not rechargeable.

This data sheet is an insert part of the Primary lithium batteries Selector Guide (ref 31048-2), where complementary information and data on features, safety and storage can be found.

Saft
Specialty Battery Group
 12, rue Sadi Carnot
 93170 Bagnolet – France
 Tel.: +33 (0)1 49 93 19 18
 Fax: +33 (0)1 49 93 19 69

www.saftbatteries.com

Doc N° 31049-2-0710
 Edition: July 2010

Data in this document is subject to change without notice and becomes contractual only after written confirmation. Single cells mentioned in this document may have their own specific data sheet with complementary data. Please check website.

Published by the Communications Department.

Photo credit: Saft.

Société anonyme au capital de 31 944 000 €

RCS Bobigny B 383 703 873

Produced by Arthur Associates Limited.



saft